



## Wrist Band Tag (Watch Type)


### FEATURES

- The wristband Tag with multi read/write capability resembles Wristwatch in shape and is elegant in look.
- Dust & waterproof
- Soft and non allergic to skin

### APPLICATIONS

- Access Control and Security in various places like Amusement Park, Clubs, Theaters etc.
- Keyless Hotel Room and Locker Entry
- Prevention of Counterfeitation
- Hospital and event management
- Customer Loyalty Programs

|                            |   |  |
|----------------------------|---|--|
| <b>Chip Type:</b>          | <b>Alien Higgs 9, GS1 Class 1 Gen 2</b>                   |  |
|                            | <b>EPC Memory:</b> Up to 496-EPC Bits (nominally 96 bits) |  |
|                            | <b>User Memory:</b> Up to 688 Bits                        |  |
|                            | <b>Data Retention:</b> 50 Years                           |  |
|                            | <b>Write Endurance:</b> 200,000 Cycles                    |  |
| <b>Mechanical:</b>         | <b>Housing Length</b>                                     | 44.5 mm  |
|                            | <b>Housing Width</b>                                      | 36.8 mm  |
|                            | <b>Housing Thickness</b>                                  | 12.0 mm  |
|                            | <b>Total length</b>                                       | 257 mm   |
|                            | <b>Strap material</b>                                     | TPU  |
|                            | <b>Weight</b>   | 23.5 gm  |
| <b>Electrical:</b>         | <b>Operating Frequency</b>                                | 865-868MHz, (902-928MHz also available on request) |
|                            | <b>Operating mode</b>                                     | Passive (battery-less transponder)                 |
| <b>Ingress Protection:</b> | IP67  |  |
| <b>Thermal:</b>            | <b>Storage Temp.</b>                                      | -25°C to +85°C                                     |
|                            | <b>Operating Temp.</b>                                    | -25°C to +85°C                                     |
| <b>Part Number:</b>        | 333V3   |  |
| <b>Options:</b>            | <b>Available with:</b>                                    |  |
|                            | Other IC type on request                                  |  |



Note: Tolerance applicable are **Length:**  $\pm 1\text{mm}$ , **Width:**  $\pm 0.5\text{mm}$  and **Thickness:**  $\pm 0.3\text{mm}$

## Tag Placement

---

- ✚ To get best performance it is strictly recommended to use circular polarized antenna.

