



30 mm Token Tags

FEATURES

- Token Tag is ATEX approved and thus can be used in potentially explosive atmosphere
- The tag with multi read/write capability is small in size & made of PC/ABS to meet all endurance requirements in terms of heat, harsh environments and chemical resistance
- Perform in the harshest environments, including harsh chemicals, painting processes & outdoor exposure.
- Dust & Waterproof.
- Flexible Read/Write Range (reader dependant).
- Insensitive to almost all non metallic materials.

APPLICATIONS

- It has been widely used in access control, supply chain, manufacturing, service industries, distribution logistics and manufacturing companies to identify goods & objects in an industrial environment.
- Can be used to read through obstructions, including water, plastics, concrete and more.
- Suitable for factory floor manufacturing applications because of rugged construction (IP Rating).

Chip Type:	I-Code SLIX 13.56 MHz, ISO/IEC 15693	
	1024 bits, organized in 32 blocks of 4 bytes each	
	Data retention of 50 years	
	Write endurance 100,000 cycles	
Mechanical:	Outer Dia.	30mm
	Thickness	3mm
	Material	PC/ABS
	Colour	Blue
	Weight	2.6 g
	Antenna Type	Wire Antenna
Electrical:	Operating Frequency	13.56 Mhz
	Operating mode	Passive (battery-less transponder)
Ingress Protection:	IP68	
Thermal:	Storage Temp.	-20 °C to +70 °C
	Operating Temp.	-20 °C to +70 °C
Part Number:	207A1-Ex	
Atex Marking details:	II 1 G, Ex ia IIC T5 Ga	
Options:	Other IC type, Size, Shape & Colour on request	
	Available with other plastic material.	

*Preliminary Data Sheet: Certain specification subject to change.