



Waste Bin Tag

FEATURES

- Perform in the harshest environments, including harsh chemicals, painting processes, outdoor exposure.
- Heavy-based construction provides both stability and safety.
- Dust & Waterproof.
- Flexible Read/Write Range (reader dependant).
- Insensitive to almost all non metallic materials.

APPLICATIONS

- Waste Bin Tag enables automatic measurement of weight of waste; promoting efficiency and control.
- In-transit tracking of Waste Management Containers and Bins.
- The movement and user duration (lifespan) of the bins and containers can be monitored within the user locations.

Chip Type:	SIC 279, 192 bit, HDX Read/write memory, 134.2KHz	
	Fully compliant with EN14803 (BDE standard) protocol	
	Data retention of 20 years	
	Write endurance 100.000 cycles	
Mechanical:	Outer Dia.	30mm
	Thickness	15.5mm
	Material	Polyamide
	Colour	Black
	Weight	12.0 g
	Antenna Type	Wire Antenna
Electrical:	Operating Frequency	134.2 KHz
	Operating mode	Passive (battery-less transponder)
Ingress Protection:	IP67	
Thermal:	Storage Temp.	-40 °C to +85 °C
	Operating Temp.	-25 °C to +85 °C
Part Number:	10851	
Options:	Other IC type, Size, Shape & Colour on request	
	Available with other plastic material e.g. PC/ABS	

*Preliminary Data Sheet: Certain specification subject to change.