




UHF CLASS 1 GEN 2 TAG SELECTION GUIDE
Ceramic Tags

UHF Tag Ceramic				
	M-Pawn Tag	M-Bishop Tag	M-Rook Tag	M-Knight Tag
Dimension (in mm)	5 x 5 x 3	10 x 5 x 3	25 x 9 x 3	25 x 25 x 3
Weight	0.4gms	0.9gms	3.6gms	8.6gms
Encasement	Durable Paint	Durable Paint	Durable Paint	Durable Paint
Frequency	865-868MHz / 902-928MHz	865-868MHz / 902-928MHz	865-868MHz / 902-928MHz	865-868MHz / 902-928MHz
Read Range	Upto 0.8 m (on metal)	Upto 1 m (on metal)	Upto 3.0 m (on metal)	Upto 10 m (on metal)
IC's Type	Higgs 3	Higgs 3	Higgs 3	Higgs 3
IP rating	IP 68	IP 68	IP 68	IP 68
Operating Temperature	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C	-40°C to +85°C
Storage temperature	-40°C to +150°C	-40°C to +150°C	-40°C to +150°C	-40°C to +150°C
Attachment method	Adhesive	Adhesive	Adhesive	Adhesive
Options	-	-	-	-
Part No.	380V1	381V1	382V1	383V1
Applications	IT Asset tracking, tool tracking etc.	IT Asset tracking, tool tracking etc.	IT Asset tracking, tool tracking etc.	IT Asset tracking, tool tracking etc.